



Pipe Size	MAXIMUM LOAD RTG. (LBS)	A	B	C	Max. Axial Travel (Inches) on Pipe Roll
	On Pipe Roll				
2 1/2	225	9	6	1/4	2
3	250	9	6	1/4	2
3 1/2	300	9	6	1/4	2
4	350	9	6	1/4	2
5	450	9	6	1/4	2
6	500	9	6	1/4	2
8	625	9	6	1/4	2
10	875	12	9	3/8	4
12	1400	12	9	3/8	4
14	1475	12	9	3/8	4
16	1650	12	9	1/2	4
18	1800	12	9	1/2	4
20	1875	12	9	1/2	4
24	2050	12	9	3/4	4
30	2250	12	9	3/4	4
36	2250	12	9	3/4	4
42	2250	12	9	3/4	4

TABLE I

Contact factory for other dimensions, temperatures, and loads. Available in all insulation thicknesses.

Hardware sold separately

Note: For higher load ratings, see A8200

The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice. Contact factory for current information.

<p>Application:</p> <p>Model A8000 is designed for use on:</p> <ul style="list-style-type: none"> · Hot Water · Cold Water · Chilled Water · Dual Temperature · Vacuum · Steam · Gas · Air <p>Intended for installation on:</p> <ul style="list-style-type: none"> · Flat Surfaces · Pipe rolls, see A7000 · Clevis hangers, see A9000 <p>Temperature Range: +40°F to +1200°F Note: Up to 1700°F available upon request.</p>	<p>Features:</p> <ul style="list-style-type: none"> · Compact · Easy installation · Eliminates welding to pipe · Copper tubing sizes available · Minimizes heat-loss and/or condensation · Insulating structural inserts for load transfer · Overlapping galvanized sheet metal jacket · Other I.D.'s and/or O.D.'s available on request · Load distribution plate integral with bottom jacket <p>Performance Test Results on File: Available upon request.</p>	<p>Material Data:</p> <ul style="list-style-type: none"> · A8000: Applicable P.S.I. spec. doc. No. 205. · Insulation: Calcium Silicate asbestos-free, treated with water repellent. · Jackets: Galvanized Steel ASTM A-527. · Structural Inserts: High-density calcium silicate asbestos-free, treated with water repellent. · Load Distribution Plate: Carbon steel ASTM A-36 · Coating: Primer coated or hot-dip galvanized. Other coatings available upon request. · Glue: Industrial contact adhesive. <p>Formal Submittal Sheets available</p>
---	--	---