



Dimensions and ratings are subject to change without notice.  
Available in all insulation thickness.

**Note:**

- For “no moment” anchor, see: C1100
- For insulated friction anchor, see: C3000
- For large bore welded anchor, see: C2000
- For insulated positive anchor, see: C4000

Pipe Size	A	C	D	Insulation Thickness						
				1"	2"	3"	4"	5"	6"	7"
				B	B	B	B	B	B	B
3	3	1.75	0.56	4	4	6	6	8	8	10
3.5	3.5	2.25	0.56	4	4	6	6	8	8	10
4	4	2.75	0.56	4	4	6	6	8	8	10
5	5	3.5	0.69	4	4	6	6	8	8	10
6	6	4.5	0.69	4	4	6	6	8	8	10

**Application:**

Model C1000 and C1030 are designed for use on:  
· Pipe Sizes through 6"

Model No.      For use with Pipe Material

C1000	Carbon Steel
C1010	Chrome-Moly
C1020	Carbon Silicon
C1030	Stainless

**Features:**

- Supplied with bolt holes for choice of bolting or welding to support structure.
- Bottom-of-pipe to top-of-steel matches base mounted insulated supports. See “B” Series.
- Broad selection of materials to match pipe material and eliminate galvanic action.

**Material Data:**

- **C1000:** A36 Carbon Steel.
- **C1010:** A387 Gr. 22 Chrome-Moly Steel.
- **C1020:** A515 Gr. 70 Carbon Silicon Steel.
- **C1030:** 304L Stainless Steel.
- **Primer Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request.

Other materials available upon request.

**Formal submittal sheets available.**