



The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice. Available in all insulation thickness.

Contact factory for current information.

Note: For higher load ratings, see: D6300.

Pipe Size	Vert load lbs.	A	B	Insul. Thk. 1"			Insul. Thk. 2"			Insul. Thk. 3"			Insul. Thk. 4"		
				C	D	E	C	D	E	C	D	E	C	D	E
				16	6600	1x4 1/2	1.25	9.31	24.875	6	10.31	26.875	9	11.31	28.875
18	7000	1x4 1/2	1.25	10.31	26.875	9	11.31	28.875	9	12.31	30.875	9	13.31	32.875	9
20	7200	1x4 1/2	1.25	11.31	28.875	9	12.31	30.875	9	13.31	32.875	9	14.31	34.875	12
24	9000	1x4 1/2	1.25	13.31	32.875	9	14.31	34.875	12	15.31	36.875	12	16.31	38.875	12
30	9600	1x4 1/2	1.25	16.31	38.875	12	17.31	40.875	12	18.31	42.875	12	19.31	44.875	12

TABLE I

### Application:

D6200 is designed for use on:

- Hot water
- Cold water
- Chilled water
- Dual temperature
- Steam
- Air
- Gas
- Vacuum

Intended to be hung from two threaded rods in close overhead clearance conditions.

### Temperature Range:

**Standard:** +40°F to +1200°F CalSil Insulation

**Note:** Up to 1800°F available upon request.

**Cryogenic:** -275°F to +275°F Urethane Insulation. Add U after the model number (i.e., D6200U)

### Features:

- Compact
- Easy installation
- Eliminates welding to pipe
- Copper tubing sizes and pipe sizes
- Overlapping galvanized sheet metal jacket
- Minimizes heat-loss and/or condensation
- Minimal overhead clearance requirement
- Other I.D.'s and/or O.D.'s available on request

Performance test results on file:  
Available upon request.

### Material Data:

- **D6200:** Applicable PSI specification document: No. 209.
- **Insulation:** Calcium silicate asbestos-free, treated with water repellant.
- **Jackets:** Galvanized steel ASTM A-653.
- **Glue:** Industrial contact adhesive
- **Structural Inserts:** High-density calcium silicate asbestos free, treated with water repellant.
- **Steel Straps:** Carbon steel ASTM A-36.
- **Fasteners:** ASTM A-307 plated.
- **Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request

**Formal submittal sheets available**